

Baumit Uniprimer

Primer

Product	Ready to use, organic based primer for hand application. A system component from the Baumit External Wall Insulation Systems EPS, Mineral and XS 022 .
Composition	Organic binders, silicon based additives, mineral fillers, additives and water.
Properties	Improves adhesion and equalizes background suction. Helps to maintain colour uniformity of Baumit topcoats and improves the hydrophobic qualities of the background.
Intended use	Universal priming coat for interiors and exteriors to prepare background surfaces before applying Baumit NanoporTop , Baumit SilikatTop , Baumit SilikonTop , Baumit GranoporTop , Baumit StyleTop , Baumit EdelPutz , and Baumit MosaikTop .
Technical data	Aggregate size: < 0.5 mm Density: ca. 1650 kg/m ³ Solids content: ca. 70% Colour: white Consumption: ca. 0.20 – 0.25 kg/m ² (1 coat application on smooth surfaces) ca. 0.40 kg/m ² (1 coat application on render basecoats)
Health and safety	Please refer to the Material Safety Data Sheet, produced in accordance with Article 31 and Annex II of Regulation No 1907/2006 of the European Parliament and Council from 18.12.2006, available at www.baumit.com or alternatively request the MSDS from the manufacturer.
Storage	Store in dry, cool conditions, free from frost in sealed tubs. Shelf life 12 months.
Quality assurance	In house monitoring through our own laboratories. Third party inspection is carried out through a certified body.
Packaging	Tub 25 kg, 1 pallet = 24 tubs = 600 kg.
Substrate	Substrates must be sound, clean, dry, free from frost, dust, efflorescence and not water repellent.

Suitable substrates:

- Mineral basecoat render on External Wall Insulation systems.
- Lime and cement renders, concrete
- Lime and gypsum plasters
- Well bonded mineral, silicate and dispersion paints and coatings

Not suitable on to:

- Fresh lime plasters and renders
- Varnish and oil films, lime paints
- Chalking and friable surfaces (remove mechanically)
- Shuttering oil on concrete formwork(remove with a steam pressure washer or standard oil removers)
- Soiled areas (clean with a steam pressure washer)
- Areas with algae growth (treat with Baumit SanierLösung)
- Peeling, weathered paint (remove mechanically)
- Damaged or cracked mineral backgrounds (apply a coating (e.g. Baumit StarContact) and where necessary embed Baumit StarTex reinforcement mesh)
- Gypsum plasterboards (pretreated with Baumit SperrGrund)

Application

Mixing:

Baumit Uniprimer must be well and slowly mixed with an electric hand mixer before application. Do not mix with other paint materials. Where required a minimal amount of water may be added to improve workability.

Apply the Uniprimer in a full and even coat with a roller or brush. Apply systematically and continuously in complete sections. Two coat applications (e.g. for irregular background suction) require a min. 24 hours drying time between coats.

Further information

The air, material and background temperature must be above +5° C during application and curing. Protect the facade from direct sunlight, rain and strong winds (i.e. with scaffold nets). High air humidity and low temperatures can prolong drying times considerably.

High air humidity and low temperatures can prolong drying times considerably and affect colour uniformity. Allow to dry 24 hours before applying further coatings.

Protective measures: Protect eyes and skin, and surrounding areas, especially glass, ceramic, brick, natural stone, varnishes and metals. Wash away any splashes with plenty of water. Do not allow to dry and harden.

Clean tools and equipment thoroughly with water immediately after use.

The information contained in this product data sheet together with any additional written or verbal information provided by Baumit is based on Baumit's previous experience of this product and reflects Baumit's current understanding of the properties of the product. However, the Customer acknowledges that the advice given in this product data sheet is not intended to be legally binding nor to create any obligation which is legally enforceable against Baumit. It is the customer's responsibility to make its own enquires and investigations into the properties and use of this product and to verify that the product is fit for the customer's intended use. Baumit reserves the right to make changes to the product without prior notice.

Baumit UK Ltd 4200 Waterside Centre, Solihull Parkway Birmingham Business Park, Birmingham. B37 7YN
tel.: +44 (0) 121-717 4843, fax: +44 (0) 121-717 4729, email: info@baumit.co.uk, web.: www.baumit.co.uk